

VITA

SERIES

SILHOUETTE

50 Δ t

(75/65/20°C)

K1



K2



Height mm	Length mm	White UIN	Colour UIN	Heat output		White UIN	Colour UIN	Heat output	
				Watts	Btu/h			Watts	Btu/h
300	500	92301105	92301105c	235	802	92302205	92302205c	449	1532
	1000	92301110	92301110c	470	1604	92302210	92302210c	898	3064
	1500	92301115	92301115c	705	2405	92302215	92302215c	1347	4596
450	400	92451104	92451104c	272	928	92452204	92452204c	509	1737
	600	92451106	92451106c	409	1396	92452206	92452206c	764	2607
	700	92451107	92451107c	477	1628	92452207	92452207c	891	3040
	800	92451108	92451108c	545	1860	92452208	92452208c	1018	3473
	900	92451109	92451109c	613	2092	92452209	92452209c	1146	3910
	1000	92451110	92451110c	681	2324	92452210	92452210c	1273	4343
	1100	92451111	92451111c	749	2556	92452211	92452211c	1400	4777
	1200	92451112	92451112c	817	2788	92452212	92452212c	1528	5214
	1400	92451114	92451114c	953	3252	92452214	92452214c	1782	6080
	1600	92451116	92451116c	1090	3719	92452216	92452216c	2037	6950
	1800	92451118	92451118c	1226	4183	92452218	92452218c	2291	7817
600	400	92601104	92601104c	348	1187	92602204	92602204c	640	2184
	600	92601106	92601106c	522	1781	92602206	92602206c	961	3279
	700	92601107	92601107c	609	2078	92602207	92602207c	1121	3825
	800	92601108	92601108c	696	2375	92602208	92602208c	1281	4371
	900	92601109	92601109c	783	2672	92602209	92602209c	1441	4917
	1000	92601110	92601110c	870	2968	92602210	92602210c	1601	5463
	1100	92601111	92601111c	957	3265	92602211	92602211c	1761	6009
	1200	92601112	92601112c	1044	3562	92602212	92602212c	1921	6554
	1400	92601114	92601114c	1218	4156	92602214	92602214c	2241	7646
	1600	92601116	92601116c	1392	4750	92602216	92602216c	2562	8742
	1800	92601118	92601118c	1566	5343	92602218	92602218c	2882	9833
	2000	92601120	92601120c	1740	5937	92602220	92602220c	3202	10925

Δ t50 is the UK's industry standard for heating outputs, which has an operating temperature of 75/65/20°C. If you have a low temperature heat source you may wish to consider Δ t40 or Δ t30 output (see your installer or system designer or download from www.stelrad.com).

For EN442 data, technical and installation information please visit our website: www.stelrad.com and search product downloads.

COLOUR OPTIONS



Comes in White as standard (RAL 9016).


Please note that once a coloured radiator has been ordered, it cannot be cancelled or returned.



www.stelrad.com
Telephone: 0800 876 6813


WALL MOUNTING AND LUG INFORMATION

All dimensions in mm. Inches in brackets.



MOUNTING BRACKETS


All dimensions in mm. Inches in brackets. Floor mounting brackets available.



Dimensions	mm	inches	mm	inches	mm	inches
Height	300	11.81	450	17.72	600	23.62
A	65	2.56	65	2.56	65	2.56
B	119	4.69	99	3.90	99	3.90
C	-	-	269	10.59	419	16.50
D	153	6.02	303	11.93	453	17.83
E	185	7.28	335	13.19	485	19.09

K1 & K2 LUG POSITIONS

All dimensions in mm. Inches in brackets.



PANEL HEIGHT

D

mm	in	mm	in
300	11.81	155	6.10
450	17.72	305	12.01
600	23.62	455	17.91
700	27.56	555	21.95

K1

K2


Dimensions	mm	in	mm	in
A 400mm	117	4.61	133	5.24
A 500 - 2000mm	150	5.91	133	5.24
B 400 - 2000mm	60	2.36	60	2.36
C 1800 - 2000mm	17	0.67	L/2	L/2

L/2 is the length divided by two.

CONNECTIONS

Each radiator comes with 1/2" inlet connections as standard.


PIPING OPTIONS



EN 442 CERTIFICATION DATA - CETIAT TESTED IN ACCORDANCE WITH BS EN 442

Type	K1			K2		
Height	300	450	600	300	450	600
W/m at 75/65/20	470	681	870	898	1273	1601
n-coefficients	1.26	1.27	1.28	1.30	1.30	1.31
Weight (kg/m)	14.13	18.22	24.27	19.30	28.85	38.40
Water contents (l/m)	1.81	2.53	3.23	3.10	4.65	6.20
K _M	3.37	4.67	5.89	5.60	7.69	9.37

PRESSURE DROPS



Type	Kv
P1 / K1	1.67
P+ / K2	3.32
K3	3.65

55 COLOUR OPTIONS. 14-DAY LEAD TIME.

Stelrad Radiators are available in white (RAL 9016) as standard, however this radiator is **now available in a variety of colours within 14 working days.**

STANDARD COLOUR




RAL 9016
Traffic white

To request up to 5 colour samples, please email sales@stelrad.com or call **0800 876 6813** with your choices and address details.

The colours shown are reproduced as accurately as this printing process will allow.

RAL COLOURS - Satin Finish



1001
Beige



1013
Oyster white



1015
Light ivory



9001
Cream



9002
Grey white




9003
Signal white




9010
Pure white



9016
Traffic white




9018
Papyrus white




9005
Jet black



9017
Traffic black



7001
Silver grey




7011
Iron grey




7015
Slate grey



7016
Anthacite grey



7030
Stone grey



7032
Pebble grey




7035
Light grey




7036
Platinum grey



7037
Dusty grey



7038
Agate grey



7039
Quartz grey




5002
Ultramarine blue



5010
Gentian blue




5012
Light blue



5014
Pigeon blue



5015
Sky blue




5022
Night blue

Please note: When a coloured radiator or radiators have been ordered they cannot be cancelled or returned.


For further information on RAL colours please visit www.ralcolorchart.com



RAL COLOURS (continued)




5024
Pastel blue




6005
Light moss green




6018
Yellow green




6019
Pastel green




6020
Chrome green



6027
Light green



6033
Mint turquoise



6034
Pastel turquoise




3000
Flame red



3002
Carmine red



3003
Ruby red



3005
Wine red



2003
Pastel orange



2008
Bright red orange



1004
Golden yellow




1016
Sulphur yellow




1021
Colza yellow




3015
Light pink




8014
Sepia



8017
Chocolate brown



7026
Granite



1019
Cappuccino




8028
Terra brown




9011
Graphite black


METALLIC



1247M
Bronze metallic



7001M
Silver metallic



9007M
Grey metallic

Please note: When a coloured radiator or radiators have been ordered they cannot be cancelled or returned.

For further information on RAL colours please visit
www.ralcolorchart.com